



JLS24UGS1-2

1-Line Uni-directional High Power TVS Diode

Jialan-Microelectronics

Description

The JLS24UGS1-2 is an Uni-directional TVS diode, utilizing leading monolithic silicon technology to provide fast re-sponse time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power lines. The JLS24UGS1-2 complies with the IEC 61000-4-2 (ESD) standard with $\pm 30\text{kV}$ air and $\pm 30\text{V}$ contact discharge. It is assembled into a SOD-123FL lead -free package. The small size and high ESD/ surge protection make JLS24UGS1-2 an ideal choice to protect cell phone, digital cameras, audio players and many other portable applications.

Circuit Diagram



Circuit and Pin Schematic

Marking Diagram



Transparent top view

24A:Device Marking Code

Features

- * 7000W peak pulse power (8/20 μs)
- * Low leakage:nA level
- * Operating voltage: 24V
- * Low clamping voltage
- * One power line protects
- * Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC61000-4-5 (Lightning) 220A (8/20 μs)
- * RoHS Compliant
- * Package: SOD-123FL

Applications

- * Fast-charge battery chargers
- * Power management system
- * Cellular Handsets and Accessories
- * Personal Digital Assistants
- * Notebooks and Handhelds
- * Portable Instrumentation
- * Digital Cameras

Ordering Information

Part Number	Packaging	Reel Size
JLS24UGS1-2	3000/Tape & Reel	7 inch



JLS24UGS1-2

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	Ppk	7000	W
Peak Pulse Current (8/20 μs)	IPP	220	A
ESD per IEC 61000-4-2 (Air)	VESD	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Operating Temperature Range	TJ	-55to +125	$^{\circ}\text{C}$
Storage Temperature Range	Tstg	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				24	V
Breakdown Voltage	V_{BR}	$I_{\text{T}} = 1\text{mA}$	25.0			V
Reverse Leakage Current	I_{R}	$V_{\text{RWM}} = 24\text{V}$			0.02	μA
Clamping Voltage	V_{C}	$I_{\text{PP}} = 100\text{A}$ (8 x 20 μs pulse)			28.5	V
Clamping Voltage	V_{C}	$I_{\text{PP}} = 220\text{A}$ (8 x 20 μs pulse)			33	V
Junction Capacitance	C_{J}	$V_{\text{R}} = 0\text{V}$, $f = 1\text{MHz}$			590	pF

Portion Electronics Parameter


Symbol	Parameter
I_{T}	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_{C}	Clamping Voltage @ I_{C}






JLS24UGS1-2


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



IEC61000-4-2 Pulse Waveform




Power Derating Curve




8 X 20us Pulse Waveform



SOD-123FL Package Outline Drawing (Dimensions in millimeters)



Suggested Land Pattern



NOTICE

Jelan-Link reserves the right to make changes without further notice to any products here in.

Only obligations are those in the Jelan-Link Standard Terms and Conditions of Sale and in no case will Jelan-Link be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.